

PATENT ABSTRACTS OF JAPAN

(11)Publication number : 09-233397

(43)Date of publication of application : 05.09.1997

(51)Int.Cl. H04N 5/44
H04N 5/45
H04N 7/025
H04N 7/03
H04N 7/035
H04N 7/173

(21)Application number : 08-033840

(71)Applicant : HITACHI LTD

(22)Date of filing : 21.02.1996


(72)Inventor : NAKAGAKI NOBUFUMI
TAKAHASHI SATOSHI
KASAHARA YASUHIRO
KOJIMA NOBORU
SUGIYAMA MASAHIRO
TERANISHI KENTARO
HOSHINO TAKASHI
HIRANO YASUHIRO

(54) INTERACTIVE TELEVISION RECEIVER

(57)Abstract:

PROBLEM TO BE SOLVED: To obtain simple operability and convenience by discriminating command information, collecting and outputting concerned information from a data file or concerned data from a broadcast station.

SOLUTION: A broadcast radio wave STV is demodulated into a video signal VS and an audio signal AS by a tuner 1. The video signal VS is demodulated by a video demodulation section 2 and decoded by an ITV processing section 7 for interactive storage information and stored. A remote commander reception section 8 and a microphone 9 receive the command information, which is given to the ITV processing section 7, in which the reception command is discriminated, and concerned information is retrieved from a data file and outputted. When the concerned information is not available, a broadcast station server 11 is automatically accessed via a telephone line 10 and concerned data are collected and outputted. An image synthesis section 3 applies synthesis processing the image signal V1 and



an interactive data V2 according to a control signal CT and displays the result. An audio synthesis section 5 applies synthesis processing and audio reproduction to the audio signal AS and interactive data A2. Thus, the simple operability and convenience are obtained.